



Performance Standard

Templeton Fire Department

TOPIC: BLITZ LINE DEPLOYMENT

TIME FRAME: 2:15

LEVEL OF COMPLEXITY Level 1

OBJECTIVE:

Condition: Given a Type 1 fire engine equipped with a 3" pre-connect quick attack line (blitz line), full PPE including SCBA, a flat area, and an operator for assistance

Behavior: Fire personnel will deploy the Blitz line and flow water

Standard: 100% accuracy within 2 minute and 15 seconds

PERFORMANCE:

Time will start when fire personnel dismounts from engine:

- Dismount engine from the SCBA jumpseat
- Deploy the Blitz line to predetermined location 75' from engine
- Form Hotel Coil using 50' minimum
- Signal operator that you are ready for water by stating "**Ready for Water**" (Verbal and Physical Call)
- Open nozzle, adjust nozzle pattern to narrow fog, and close nozzle

Time stops when fire personnel shuts down nozzle

- Assist with draining and re-loading of the hoseload (not included in time standard)

NOTES:

Automatic Fail

- Not clearing all hose from hosebed
- Loss of control of hose loops
- Loss of control of nozzle
- Unable to reload hose load correctly
- If participant is unable to complete standard within the time allotted

Performance standards are designed to assure that all fire personnel are capable of completing the duties assigned to their respective position. All personnel should remember that while engaging in firefighting operations, the order and/or priority of some tasks may be changed by the company officer.