

Performance Standard

Templeton Fire Department

TOPIC: WILDLAND PROGRESSIVE HOSELAY (3 PERSON)

TIME FRAME: 6:00

LEVEL of COMPLEXITY: Level 3

BEHAVIORAL OBJECTIVE:

Condition: Given a 3 person engine company, a wildland fire apparatus,

full wildland PPE, and a large flat area

Behavior: The engine company will complete a 600' progressive hoselay

Standard: 100% accuracy within 6 minutes

PERFORMANCE: Time will start when the Maxi is set:

Captain:

Perform a Size Up

Transmit a Report on Conditions, Pass Command

Don Hosepack

Determine and verbalize escape routes and safety zones

• Advance hoseline, add hose when needed

Continue to assist Firefighter to 600'

Engineer:

- Spot apparatus
- Place pump in gear
- Open Tank Fill and Place a chock block
- Establish anchor point with reel line
- Assist Captain/Firefighter with flaking out the hose
- Charge hoseline (200' 1 ½" SJ @ 20 GPM)
- Advance hoseline, add hose when needed
- Retreat to engine after 300', Check pump and pressure

Firefighter:

- Don Hosepack
- Deploy hoseline with a predetermined fireline 30' away from the engine's driver side
- Call for water, Remove kinks, Check nozzle pattern

Performance standards are designed to assure that all fire personnel are capable of completing the duties assigned to their respective position. All personnel should remember that while engaging in firefighting operations, the order and/or priority of some tasks may be changed by the company officer.



Performance Standard

Templeton Fire Department

Firefighter Cont...

- Assure/Complete anchor point
- Advance hoseline, Add hose when needed
- Continue to assist Captain to 600'

Time stops when last section of hose is stretched

NOTES:

Automatic Fail

- If any participant cannot complete their given tasks
- If the Engine Company cannot complete the standard within the given time